

## SHARLU TURBO XP MOTOR OIL

**SAE Viscosity Grade** : 20W/50

**Performance Level** : SG/CD  
CCMC G4/PD-2, MIL-L-46152D

**Product Description** **Sharlu Turbo XP Motor Oil** is a motor oil designed to meet the most severe requirements of modern high performance engines. It is formulated from selected high quality base stocks and excellent performing additives. It contains superior detergent/dispersants, anti-oxidant, anti-wear and corrosion inhibitors. It also contains high quality viscosity index improvers which has outstanding stay in grade performance.

**Main Benefits**

- One product for both gasoline and diesel engines.
- Excellent engine protection under severe driving conditions.
- Extended engine life and better fuel economy.

**Application** **Sharlu Turbo XP Motor Oil** is recommended for use in gasoline or diesel fuelled naturally aspirated and turbo charged automotive engines and light trucks such as taxis, and light vehicles used in commercial business.

| Physical Characteristics  | Test Method | Typical Value |
|---------------------------|-------------|---------------|
| <b>SAE Grade</b>          |             | <b>20W/50</b> |
| Specific Gravity 60/60 °F | ASTM D-4052 | 0.8920        |
| Kinematic Viscosity, cSt  | ASTM D-445  |               |
| @ 40 °C cSt               |             | 153.40        |
| @ 100 °C cSt              |             | 17.50         |
| Viscosity Index           | ASTM D-2270 | 125           |
| Pour Point, °C            | ASTM D-97   | -24           |
| Flash Point COC, °C       | ASTM D-92   | 234           |
| TBN mgm KOH/gm            | ASTM D-2896 | 6.50          |